



**NEW DESIGN**

# MJ-HD2500PRO


With 2-18pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A




Auto Anti-collision System to avoid damage




Independent constant temperature heating control ink supply system



None after-service negative Ink supply system



Printing material automatic height detection device




Using domestic BYHX in the forefront of inkjet printing control system








## Printhead Resolution

Konica1024i

Konica1024i	 <table border="1"> <thead> <tr> <th colspan="2">1*CMYK</th> <th colspan="2">4 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>33m<sup>2</sup>/h</td> <td colspan="2">1016x720</td> </tr> <tr> <td>6pass</td> <td>25m<sup>2</sup>/h</td> <td colspan="2">1016x1080</td> </tr> </tbody> </table>	1*CMYK		4 pcs			Print Speed	DPI		4pass	33m <sup>2</sup> /h	1016x720		6pass	25m <sup>2</sup> /h	1016x1080	
	1*CMYK		4 pcs														
		Print Speed	DPI														
	4pass	33m <sup>2</sup> /h	1016x720														
	6pass	25m <sup>2</sup> /h	1016x1080														
 <table border="1"> <thead> <tr> <th colspan="2">2*CMYK</th> <th colspan="2">8 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>48m<sup>2</sup>/h</td> <td colspan="2">1016x720</td> </tr> <tr> <td>6pass</td> <td>36m<sup>2</sup>/h</td> <td colspan="2">1016x1080</td> </tr> </tbody> </table>	2*CMYK		8 pcs			Print Speed	DPI		4pass	48m <sup>2</sup> /h	1016x720		6pass	36m <sup>2</sup> /h	1016x1080		
2*CMYK		8 pcs															
	Print Speed	DPI															
4pass	48m <sup>2</sup> /h	1016x720															
6pass	36m <sup>2</sup> /h	1016x1080															
 <table border="1"> <thead> <tr> <th colspan="2">2*CMYK+2W</th> <th colspan="2">10 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>47m<sup>2</sup>/h</td> <td colspan="2">1016x720</td> </tr> <tr> <td>6pass</td> <td>35m<sup>2</sup>/h</td> <td colspan="2">1016x1080</td> </tr> </tbody> </table>	2*CMYK+2W		10 pcs			Print Speed	DPI		4pass	47m <sup>2</sup> /h	1016x720		6pass	35m <sup>2</sup> /h	1016x1080		
2*CMYK+2W		10 pcs															
	Print Speed	DPI															
4pass	47m <sup>2</sup> /h	1016x720															
6pass	35m <sup>2</sup> /h	1016x1080															
 <table border="1"> <thead> <tr> <th colspan="2">3*CMYK</th> <th colspan="2">12 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>68m<sup>2</sup>/h</td> <td colspan="2">1016x720</td> </tr> <tr> <td>6pass</td> <td>45m<sup>2</sup>/h</td> <td colspan="2">1016x1080</td> </tr> </tbody> </table>	3*CMYK		12 pcs			Print Speed	DPI		4pass	68m <sup>2</sup> /h	1016x720		6pass	45m <sup>2</sup> /h	1016x1080		
3*CMYK		12 pcs															
	Print Speed	DPI															
4pass	68m <sup>2</sup> /h	1016x720															
6pass	45m <sup>2</sup> /h	1016x1080															
 <table border="1"> <thead> <tr> <th colspan="2">2*CMYK LC LM W</th> <th colspan="2">14 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>47m<sup>2</sup>/h</td> <td colspan="2">1016x720</td> </tr> <tr> <td>6pass</td> <td>35m<sup>2</sup>/h</td> <td colspan="2">1016x1080</td> </tr> </tbody> </table>	2*CMYK LC LM W		14 pcs			Print Speed	DPI		4pass	47m <sup>2</sup> /h	1016x720		6pass	35m <sup>2</sup> /h	1016x1080		
2*CMYK LC LM W		14 pcs															
	Print Speed	DPI															
4pass	47m <sup>2</sup> /h	1016x720															
6pass	35m <sup>2</sup> /h	1016x1080															

RICOH G5/G6

RICOH G5/G6	 <table border="1"> <thead> <tr> <th colspan="2">1*CMYK W</th> <th colspan="2">3 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>28m<sup>2</sup>/h</td> <td colspan="2">720x600</td> </tr> <tr> <td>6pass</td> <td>21m<sup>2</sup>/h</td> <td colspan="2">720x900</td> </tr> </tbody> </table>	1*CMYK W		3 pcs			Print Speed	DPI		4pass	28m <sup>2</sup> /h	720x600		6pass	21m <sup>2</sup> /h	720x900	
	1*CMYK W		3 pcs														
		Print Speed	DPI														
	4pass	28m <sup>2</sup> /h	720x600														
	6pass	21m <sup>2</sup> /h	720x900														
	 <table border="1"> <thead> <tr> <th colspan="2">1*CMYK W V</th> <th colspan="2">4 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>27m<sup>2</sup>/h</td> <td colspan="2">720x600</td> </tr> <tr> <td>6pass</td> <td>20m<sup>2</sup>/h</td> <td colspan="2">720x900</td> </tr> </tbody> </table>	1*CMYK W V		4 pcs			Print Speed	DPI		4pass	27m <sup>2</sup> /h	720x600		6pass	20m <sup>2</sup> /h	720x900	
1*CMYK W V		4 pcs															
	Print Speed	DPI															
4pass	27m <sup>2</sup> /h	720x600															
6pass	20m <sup>2</sup> /h	720x900															
 <table border="1"> <thead> <tr> <th colspan="2">2*CMYK+1W</th> <th colspan="2">5 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>40m<sup>2</sup>/h</td> <td colspan="2">720x600</td> </tr> <tr> <td>6pass</td> <td>33m<sup>2</sup>/h</td> <td colspan="2">720x900</td> </tr> </tbody> </table>	2*CMYK+1W		5 pcs			Print Speed	DPI		4pass	40m <sup>2</sup> /h	720x600		6pass	33m <sup>2</sup> /h	720x900		
2*CMYK+1W		5 pcs															
	Print Speed	DPI															
4pass	40m <sup>2</sup> /h	720x600															
6pass	33m <sup>2</sup> /h	720x900															
 <table border="1"> <thead> <tr> <th colspan="2">3*CMYK</th> <th colspan="2">6 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>55m<sup>2</sup>/h</td> <td colspan="2">720x600</td> </tr> <tr> <td>6pass</td> <td>42m<sup>2</sup>/h</td> <td colspan="2">720x900</td> </tr> </tbody> </table>	3*CMYK		6 pcs			Print Speed	DPI		4pass	55m <sup>2</sup> /h	720x600		6pass	42m <sup>2</sup> /h	720x900		
3*CMYK		6 pcs															
	Print Speed	DPI															
4pass	55m <sup>2</sup> /h	720x600															
6pass	42m <sup>2</sup> /h	720x900															
 <table border="1"> <thead> <tr> <th colspan="2">3*CMYK+2W</th> <th colspan="2">8 pcs</th> </tr> <tr> <th></th> <th>Print Speed</th> <th colspan="2">DPI</th> </tr> </thead> <tbody> <tr> <td>4pass</td> <td>55m<sup>2</sup>/h</td> <td colspan="2">720x600</td> </tr> <tr> <td>6pass</td> <td>42m<sup>2</sup>/h</td> <td colspan="2">720x900</td> </tr> </tbody> </table>	3*CMYK+2W		8 pcs			Print Speed	DPI		4pass	55m <sup>2</sup> /h	720x600		6pass	42m <sup>2</sup> /h	720x900		
3*CMYK+2W		8 pcs															
	Print Speed	DPI															
4pass	55m <sup>2</sup> /h	720x600															
6pass	42m <sup>2</sup> /h	720x900															

Print Software	Caldera/Photoprint	All-In-One Computer Configurations	8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen
Print Modes	Max 4 rows, match all production need		
Machine Functions	Movable folder platform, Lack ink alarm, Anti-collision device, Independent Ink heating control, Neagtive inksupply, Print height sensor	Print Colors	CMYK LC LM W V
Printing Heads	2-18pcs Ricoh Gen5/Gen6/Konica 1024i /Konica 1024A	Working Environment	5000W Electricity Power, 20°C-28°C humidty40%-70%
Machine Configurations	THK Guiderail, Leadshine Motor, BYHX Board, Germany imported tank chain, All-In-One Computer(optional)	Package Info	4626*1550*1600mm,2500KG