




# MJ-2500Z

With 2-18pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A



Auto Anti-collision System to avoid damage




Independent constant temperature heating control ink supply system



None after-service negative Ink supply system



Printing material automatic height detection device



Using domestic BYHX in the forefront of inkjet printing control system

## Printhead Resolution

Konica1024i



| 1*CMYK | 4 pcs               |           |
|--------|---------------------|-----------|
|        | Print Speed         | DPI       |
| 4pass  | 33m <sup>2</sup> /h | 1016x720  |
| 6pass  | 25m <sup>2</sup> /h | 1016x1080 |




| 2*CMYK | 8 pcs               |           |
|--------|---------------------|-----------|
|        | Print Speed         | DPI       |
| 4pass  | 48m <sup>2</sup> /h | 1016x720  |
| 6pass  | 36m <sup>2</sup> /h | 1016x1080 |



| 2*CMYK+2W | 10 pcs              |           |
|-----------|---------------------|-----------|
|           | Print Speed         | DPI       |
| 4pass     | 47m <sup>2</sup> /h | 1016x720  |
| 6pass     | 35m <sup>2</sup> /h | 1016x1080 |



| 3*CMYK | 12 pcs              |           |
|--------|---------------------|-----------|
|        | Print Speed         | DPI       |
| 4pass  | 68m <sup>2</sup> /h | 1016x720  |
| 6pass  | 45m <sup>2</sup> /h | 1016x1080 |



| 2*CMYK LC LM W | 14 pcs              |           |
|----------------|---------------------|-----------|
|                | Print Speed         | DPI       |
| 4pass          | 47m <sup>2</sup> /h | 1016x720  |
| 6pass          | 35m <sup>2</sup> /h | 1016x1080 |



| 1*CMYK W | 3 pcs               |         |
|----------|---------------------|---------|
|          | Print Speed         | DPI     |
| 4pass    | 28m <sup>2</sup> /h | 720x600 |
| 6pass    | 21m <sup>2</sup> /h | 720x900 |




| 1*CMYK W V | 4 pcs               |         |
|------------|---------------------|---------|
|            | Print Speed         | DPI     |
| 4pass      | 27m <sup>2</sup> /h | 720x600 |
| 6pass      | 20m <sup>2</sup> /h | 720x900 |



| 2*CMYK+1W | 5 pcs               |         |
|-----------|---------------------|---------|
|           | Print Speed         | DPI     |
| 4pass     | 40m <sup>2</sup> /h | 720x600 |
| 6pass     | 33m <sup>2</sup> /h | 720x900 |



| 3*CMYK | 6 pcs               |         |
|--------|---------------------|---------|
|        | Print Speed         | DPI     |
| 4pass  | 55m <sup>2</sup> /h | 720x600 |
| 6pass  | 42m <sup>2</sup> /h | 720x900 |



| 3*CMYK+2W | 8 pcs               |         |
|-----------|---------------------|---------|
|           | Print Speed         | DPI     |
| 4pass     | 55m <sup>2</sup> /h | 720x600 |
| 6pass     | 42m <sup>2</sup> /h | 720x900 |

RICOH G5/G6

|                        |                                                                                                                                          |                                    |                                                                                |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--------------------------------------------------------------------------------|
| Print Software         | Caldera/Photoprint                                                                                                                       | All-In-One Computer Configurations | 8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen |
| Print Modes            | Max 4 rows, match all production need                                                                                                    |                                    |                                                                                |
| Machine Functions      | Movable folder platform, Lack ink alarm, Anti-collision device, Independent Ink heating control, Neagtive inksupply, Print height sensor | Print Colors                       | CMYK LC LM W V                                                                 |
| Printing Heads         | 2-18pcs Ricoh Gen5/Gen6/Konica 1024i /Konica 1024A                                                                                       | Working Environment                | 5000W Electricity Power, 20°C-28°C humidty40%-70%                              |
| Machine Configurations | THK Guiderail, Leadshine Motor, BYHX Board, Germany imported tank chain, All-In-One Computer(optional)                                   | Package Info                       | 4626*1550*1600mm,2500KG                                                        |