




MJ-3200

With 3-24 pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A



Auto Anti-collision System to avoid damage



Independent constant temperature heating control ink supply system



None after-service negative Ink supply system



Printing material automatic height detection device



Using domestic BYHX in the forefront of inkjet printing control system

Printhead Resolution

Konica1024i



1*CMYK W		4 pcs
	Print Speed	DPI
4pass	33m ² /h	1016x720
6pass	25m ² /h	1016x1080



1*CMYK W V		6 pcs
	Print Speed	DPI
4pass	33m ² /h	1016x720
6pass	25m ² /h	1016x1080



2*CMYK		8 pcs
	Print Speed	DPI
4pass	48m ² /h	1016x720
6pass	36m ² /h	1016x1080



2*CMYK+2W		10 pcs
	Print Speed	DPI
4pass	47m ² /h	1016x720
6pass	35m ² /h	1016x1080



3*CMYK		12 pcs
	Print Speed	DPI
4pass	68m ² /h	1016x720
6pass	45m ² /h	1016x1080

RICOH G5/G6



1*CMYK W		3 pcs
	Print Speed	DPI
4pass	28m ² /h	720x600
6pass	21m ² /h	720x900



1*CMYK W V		4 pcs
	Print Speed	DPI
4pass	27m ² /h	720x600
6pass	20m ² /h	720x900



2*CMYK+1W		5 pcs
	Print Speed	DPI
4pass	40m ² /h	720x600
6pass	33m ² /h	720x900



3*CMYK		6 pcs
	Print Speed	DPI
4pass	55m ² /h	720x600
6pass	42m ² /h	720x900



3*CMYK+2W		8 pcs
	Print Speed	DPI
4pass	55m ² /h	720x600
6pass	42m ² /h	720x900

Print Software	Caldera/Phototprint	All-In-One Computer Configurations	8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen
Print Modes	Max 4 rows, match all production need		
Machine Functions	Movable folder platform, Lack ink alarm, Anti-collusion device, Independent Ink heating control, Neagtive inksupply, Print height sensor	Print Colors	CMYK W V/Fluorecent Colors
Printing Heads	3-24pcs Ricoh Gen5/Gen6/Konica 1024i /Konica 1024A	Working Environment	5000-8000W Electricity Power, 25°C-30°C humidty50%-70%
Machine Configurations	THK Guiderail, Leadshine Motor, BYHX Board, Germany imported tank chain, All-In-One Computer(optional)	Package Info	5560*1500*1780mm,3000KG