



MJ-3300D

With 4-24 pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A



4 serperated suction area to ensure continous printing job

1500W advanced Leadshine stable power servo motor

Advanced magnetic levitation transmission is standard

Intergrated anti-static device to improve machine stability

Special design to prevent material from wrinkling

Printhead Resolution

Konica1024i

1*CMYK W		5 pcs
	Print Speed	DPI
4pass	33m ² /h	1016x720
6pass	25m ² /h	1016x1080

2*CMYK		8 pcs
	Print Speed	DPI
4pass	48m ² /h	1016x720
6pass	36m ² /h	1016x1080

2*CMYK+2W		10 pcs
	Print Speed	DPI
4pass	33m ² /h	1016x720
6pass	25m ² /h	1016x1080

3*CMYK		12 pcs
	Print Speed	DPI
4pass	68m ² /h	1016x720
6pass	45m ² /h	1016x1080

4*CMYK		16 pcs
	Print Speed	DPI
4pass	95m ² /h	1016x720
6pass	70m ² /h	1016x1080

RICOH G5/G6

1*CMYK W		3 pcs
	Print Speed	DPI
4pass	30m ² /h	720x600
6pass	24m ² /h	720x900

1*CMYK W V		4 pcs
	Print Speed	DPI
4pass	30m ² /h	720x600
6pass	24m ² /h	720x900

2*CMYK+1W		5 pcs
	Print Speed	DPI
4pass	42m ² /h	720x600
6pass	35m ² /h	720x900

3*CMYK		6 pcs
	Print Speed	DPI
4pass	58m ² /h	720x600
6pass	46m ² /h	720x900

3*CMYK+2W		8 pcs
	Print Speed	DPI
4pass	58m ² /h	720x600
6pass	46m ² /h	720x900

Print Software	Caldera/Photoprint	All-In-One Computer Configurations	8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen
Print Modes	Max 4 rows, match all production need		
Machine Functions	Movable folder platform, Lack ink alarm, Anti-collision device, Independent Ink heating control, Neagtive ink supply, Print height sensor, 4 seperated suction area	Print Colors	CMYK LC LM W V
Printing Heads	4-24pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A	Working Environment	5510*1708*1675mm,6000W Electricity Power, 20°C-28°C humidty40%-70%
Machine Configurations	THK Guiderail, Leadshine Motor, BYHX Board, Germany imported tank chain, All-In-One Computer(optional)	Package Info	5650*1850*1950mm, 4300KG