




MJ-5200Z

With 8-40 pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A



Adapt to different diameter material by adjusting air pressure inside rollers



Branded accessories used for high attrition areas



Integrated Big functional machine control centre for high-efficiency



Rigorous ink filtration design effectively avoid impurities from going into the ink supply system



Support max 40 or more OEM konica printheads with higher speed

Printhead Resolution

Konica1024i



2*CMYK 8 pcs

	Print Speed	DPI
4pass	55m ² /h	1016x720
6pass	42m ² /h	1016x1080



2*CMYK W 10 pcs

	Print Speed	DPI
4pass	55m ² /h	1016x720
6pass	42m ² /h	1016x1080




3*CMYK 12 pcs

	Print Speed	DPI
4pass	75m ² /h	1016x720
6pass	58m ² /h	1016x1080



3*CMYK LC LM 18 pcs

	Print Speed	DPI
4pass	75m ² /h	1016x720
6pass	58m ² /h	1016x1080



4*CMYK LC LM 24 pcs

	Print Speed	DPI
4pass	98m ² /h	1016x720
6pass	80m ² /h	1016x1080



3*CMYK W 15 pcs

	Print Speed	DPI
4pass	75m ² /h	1016x720
6pass	58m ² /h	1016x1080



6*CMYK 24 pcs

	Print Speed	DPI
4pass	180m ² /h	1016x720
6pass	108m ² /h	1016x1080



6*CMYK LC LM 36 pcs

	Print Speed	DPI
4pass	180m ² /h	1016x720
6pass	108m ² /h	1016x1080

Print Software	Caldera/Photoprint	All-In-One Computer Configurations	8th Generations i7-8750H Processor, 64G/128G, 15.6-inch 1920x1080 Touch Screen
Print Modes	Max 6 rows, match all production need		
Machine Functions	Movable folder platform, Lack ink alarm, Anti-collusion device, Independent Ink heating control, Neagtive ink supply, Print height sensor	Print Colors	CMYK LC LM W V
Printing Heads	8-40pcs Ricoh Gen5/Gen6/Konica 1024i/Konica 1024A	Working Environment	6000W Electricity Power, 20°C-28°C humidity40%-70%
Machine Configurations	THK Guiderail, Leadshine Motor, BYHX Board, Germany imported tank chain, All-In-One Computer(optional)	Package Info	7880*2084*1846mm,4500KG